

Technical Data

STEAMBIO, the steam cleaning solution in industries

www.iblspecifik.com - contact@iblspecifik.com



DESCRIPTION	RANGE		
	STEAMBIO 10000, 19000, 30000		
	10kW	19.5kW	30kW
Supply (V-Hz)	400-50	400-50	400-50
Max motor unit absorption (kW)	10	19.5	30
Absorption power (Amperes)	15	28.5	44.1
Time switch (Minutes)	7	7	7
Water tank	Yes	Yes	Yes
Boiler			
Boiler capacity (Liters)	6.6	16	16
Structure	304 Stainless steel	304 Stainless steel	304 Stainless steel
Boiler power (Watts)	10,000	19,500	30,000
Steam			
Steam output (g/min)	230	416	667
Work pressure (Bars)	10	10	10
Steam temperature inside boiler (°C)	180	180	180
Water / Detergent			
Water output from water /detergent pump	Yes	Yes	Yes
Control of water / detergent output	No	No	No
Tanks			
Water tank material	PET	PET	PET
Water tank capacity (Litres)	11	25	25
Detergent tank material	PET	PET	PET
Detergent tank capacity (Litres)	11	5	5
Vacuum			
Vacuum plug	Optional	Optional	Optional
Machine size			
Length (mm)	1,050	1,050	1,050
Width (mm)	500	500	500
Height (mm)	970	970	970
Weight (kg)	92	113	124,5



www.iblspecifik.com - contact@iblspecifik.com

READ CAREFULLY THE USER MANUAL BEFORE USING